



MONITOR

Stainless Steel Industrial Monitor

Endurance and reliability

Features	XM7W7	XM712	XM715	XM719
Display Size	7" Wide	12,1"	15"	19"
Bezel Inox V2A	6mm thickness			
Technology	TFT 262 K colors		TFT 16,2 M colors	TFT 16,7 M colors
Display Backlight	LED			
Brightness cd/m2	500	370	350	400
Contrast	600:1		700:1	1000:1
Viewing angle H-V	70-60		140-120	170-170
Lamp life (min a 25°C)	50k			
Resolution (pixel)	800 x 480	800 x 600	1024 x 768	1280 x 1024
Touch technology	Analog resistive true flat (4 wires)		Analog resistive true flat (5 wires)	
Touch output	RS232 + USB			
USB frontal IP66 / USB rear (2.0)	None			
Green Led Power ON	None			
VGA/DVI-I */S-Video/Video composite	1 x (* digital signal only single-link)			
External (WxHxD)	228 x 155 x 66,7	336 x 256 x 56,7	425 x 300 x 57,2	508 x 384 x 64,2
Cut-out (WxH)	219 x 145	321 x 240	393 x 275	477 x 353
Power supply (Vdc)	18...30 max 50W			
Power consumption (W)	30	35		45
Protection degree	IP69K front 7" / 12,1" - IP66 front 15" / 19"			
Operating temperature (°C)	0...50 (non condensing)			
Storage temperature (°C)	-20...+65			
Humidity	90% (non condensing)			
Weight (Kg)	3,0	5,0	7,0	10,5
Certifications	CE / ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 Environmental EN60068-2-6/27/30 / Immunity EN61000-6-2 / Emission EN 61000-6-4			